

LITETECH TRADITIONAL OUTDOOR PRODUCTS

AREA LIGHT

	<p>Specification Features:</p> <p>Housing: Die-cast aluminium housing. Stainless steel screws. Durable silicon rubber gasket. Finished in corrosion, acid and anti-ageing resistant powder paint in various colours with Chromatized Protection.</p> <p>Diffuser: Opal Polycarbonate / Glass diffuser / High Impact Acrylic/ Clear PMMA.</p> <p>Reflector: Anodized High Purity Aluminium.</p> <p>Control Gear: Certified as per European Safety Standard.</p> <p>Wiring: All wiring, socket and connectors are heat resistant and meet European Safety Standard requirements.</p> <p>IP Rating: IP54/ IP65</p> <p>Installation: Pole is root mounted in the ground. Decorative lantern is fixed to the post top. Street lantern can be fixed both side and top entry on the pole.</p>
<p>PRODUCT DESCRIPTION:</p> <p>A wide variety of low maintenance architectural area lights and street avenue lights mounted on poles. It consists of a post on which a decorative lantern is mounted. Suitable for outdoor application as it is ensured high ingress protection.</p>	

BOLLARD



PRODUCT DESCRIPTION:

Excellent series of Bollards and Pillar Lights for Outdoor boundary, Pillars and Garden lighting with symmetrical or asymmetrical light distribution.

Specification Features:

Housing: The housing is made of extruded aluminium column.
Anodized high purity aluminium reflector/ steel white painted reflector.

Finished in Outdoor high corrosion resistant powder paint and chromatised protection.

Stainless steel screws.

Diffuser: Polycarbonate Diffuser.

Control Gear: Certified as per European Safety Standard.

Wiring: All wiring, socket and connectors are heat resistant and meet European Safety Standard requirements.

IP Rating: IP65

Installation: The fitting is provided with J type mounted plate which anchors the counter flange tightly for quick and easy installation.



The power supply wire must be at least 0.8 meter above the ground surface.

BULK HEAD



PRODUCT DESCRIPTION:

This series constitutes a range of robust general purpose bulkhead series surface mounted wall luminaires in round, square, square with conical top, square with rounded edges and oval shapes with a variety of options in grills and visors for indoor and outdoor lighting.

Specification Features:

Housing:

The body is of die-cast aluminium or Polycarbonate.

Stainless steel screws.

Durable silicon rubber gasket.

Finished in sandy texture with high corrosion resistant powder paint (in the colours: Silver-grey, white and black) and Chromatized protection.

Diffuser:

Opal Polycarbonate or Glass diffuser.

Control Gear:

Certified as per European Safety Standard.

Wiring:

All wiring, socket and connectors are heat resistant and meet European Safety Standard requirements.

IP Rating:

IP 54/ IP65

Accessories

EL3 - Emergency kit

Option:

C - Capacitor